



M3 OX10 1G

Top Rated Multi-Functional Handheld

1GHz CPU
 Multi OS Support: Windows Mobile & Windows CE
 HSPA+ / EDGE / GPRS / GSM
 Integrated RFID Reader (HF / UHF)

Key Features



1GHz CPU



Windows Embedded Handheld 6.5/
 Windows CE 6.0



Integrated RFID Reader (HF / UHF)



IEEE 802.11 a/b/g/n



Multi-mode Radio
 (802.11 a/b/g/n, Bluetooth)



IP65 / 1.5m Drop



1D Laser, 2D imager

Applications



Manufacturing



Retail



Public



Logistics



Construction



Meter Reading

Specification

Physical Characteristics

DIMENSION (W x H x D mm)	78.6 x 165.5 x 24.9
	78.6 x 165.5 x 40.2 (with HF reader)
	78.6 x 165.5 x 38.9 (with UHF reader)
WEIGHT	332g/11.7oz.
	362g/12.7oz. (with HF)
	389g/13.7oz. (with UHF)
DISPLAY (3.5" LCD)	VGA (480x640)
	QVGA (240x320)
BATTERY	Li-Ion 3.7V 3,300mA, Smart Battery

Performance Characteristics

MULTI-PROCESSOR	CPU 1 GHz
OS	Windows Embedded Handheld 6.5
	Windows CE 6.0
MEMORY	RAM 512 MB
	ROM 4 GB
	Card Slot Micro SD
INTERFACE	USB Host 1.1 / Client 2.0

User Environment

TEMPERATURE	Operating -20 to 60°C / -4 to 122°F
	Storing -30 to 70°C / -22 to 158°F
HUMIDITY	93% non-condensing
TUMBLE TEST	1,000 1.6 ft. / 0.5 m tumbles (2,000 drops)
DROP TEST	1.5m / 5ft.
IP RATING	IP65

Wireless Radio Options

WWAN	2G	GSM / GPRS / EDGE: Quad band (850 / 900 / 1800 / 1900 MHz)
	3.5G	UMTS / HSPA+: Five band (800/850/AWS/1900/2100 MHz)
WLAN	IEEE 802.11 a/b/g/n	
SECURITY	WEP, WPA, WPA2, TKIP, AES, EAP-FAST, EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-TLS, PEAP-MSCHAPv2, LEAP, CCXv4	
BLUETOOTH	Class II, V2.1 (With EDR)	
RFID	HF	13.56 MHz
	Tags	ISO 14443 A/B, ISO 15693, ISO 18000-3, I-CODE
	SAM	1 SAM / 2 SAM (optional)
	UHF	868~956 MHz
	Tags	EPC C1 G2
GPS	AGPS, GLONASS	

General Options

SCANNER	1D Laser, 2D Imager
CAMERA	5.0MP Auto Focus camera
KEYPAD	Alpha-Numeric 31 keys
	QWERTY 50 keys (WM6.5 only)

* The contents of this brochure were written based on the "current state" of the product, and the details are subject to change without the prior notice.

Detailed Features



Windows Embedded Handheld 6.5 / Windows CE 6.0

Windows Embedded Handheld 6.5 or Windows CE 6.0 is available in M3 OX10 1G.



Multi-mode Radio (802.11 a/b/g/n, 3.8G HSPA+)

Wireless data transmission through 802.11b/g/n, HSPA+ and Bluetooth.

Maximum Mobility

Tough & Rugged



IP65 / 1.5m Drop MIL-STD-810G

M3 OX10 1G is suitable to use in a tough environment : withstands drop from 1.5m and protects against dust and water.



Powerful System and Core

1GHz CPU

Powerful CPU speed with “High-Tier” guarantees faster graphic process and memory access.



5.0MP AF camera

High resolution and auto focused functionality capture ar images of product and / or cumentation.

Maximum Data Capture



1D / 2D RFID – UHF/HF (Optional)

Superior scanner / internal RFID application provides real-time data capture and automatic data processing so that you can expect flexibility of work and cost-efficiency.

Smart Battery

User Comfort



Multi-function Keypads

Multi-functional keys of QWERTY keypads are designed for versatile performance.

As hot keys, these are going to make direct access be possible and increase the user working speed.



Li-Ion 3,7V 3,300mAh

M3 OX10 1G smart battery provides accurate remaining battery capacity so that the user can efficiently plan the usage of the PDA.

O
X
1
0

M3 US20X | US20W

Lightweight and rugged mobile handheld computer



- Android 10 GMS/AER
- 2.2GHz Octa core CPU
- 3 types keypad – 30/42/51
- 2D Imager, Long-range Scanner
- Fast charging / Battery Hot Swap
- 16 MP Auto Focus Camera

M3 Mobile's US20 series is a lightweight, rugged mobile handheld computer that helps you handle your work more efficiently than ever before in the retail market as well as in the transportation and logistics. The US20 series supports the Android 10 operating system with a high-end CPU, has customized displays and a variety of keypads, and offers many advantages, including a 16 MP rear camera. Also, the application solution, M3 SPEEDPACK (M3 application package) can be used to improve and manage device performance. The US20 series is waiting for users with a variety of scanner options, complete battery design, secure Android security support, and tremendous benefits.

Support 2.2 GHz Octacore processor and Android 10 platform

With the 2.2 GHz Octa-core processor and support for the Android 10 platform, users can upgrade their productivity and efficiency.

Ergonomic Design, easy handling

Easy to use with its lightweight, neat design and flexible curve aesthetics. Additionally, the display and the three keypads are designed with a sense of unity.

Best application solution, M3 SPEEDPACK

M3 SPEEDPACK, an application solution developed by M3 Mobile. With this, you can fully manage your device. If you using the StartUp tool in M3 SPEEDPACK then the user can scan a few barcodes through your PC and device then thousands of devices can be customized and set up at once. Moreover, productivity and efficiency can be increased through various application tools.

Data Capture

It supports a wide range of scanning options from 2D to Long-Range Scanner which can do reading by using the best scan engine, and It supports normal scanner engine also. Multi barcode reading is possible. It captures barcodes at once in any environment.

User friendly Power as an option

By providing a 6,700mAh high-capacity battery, you can work all day long. The charging cradle and battery toaster enable faster and safer battery use than ever before. It also supports hot-swap functionality, allowing you to exchange batteries with confidence without turning off the device or shutting down the running app. 2,600mAh battery is ready for user who need light equipment.

Android security and update support

M3 Mobile continues to provide security updates to help secure the device from the operating system, as well as future Android versions based on Google policy like GMS and AER.

Specification

Physical Characteristics	
Dimensions	74 * 197.2 * 35.3mm / 2.91 * 7.76 * 1.38inch
Weight	450g / 15.8oz (LR Scanner with Extended battery) 416g / 14.6oz (2D Scanner with Extended battery) 403g / 14.2oz (LR Scanner with Standard battery) 369g / 13oz (2D Scanner with Standard battery)
Display	4.0" WVGA IPS, 480 x 800 pixels, Color Display
Touchpanel	Corning Gorilla Glass supports dual input mode with finger, gloved finger and stylus (conductive stylus sold separately)
Backlight	LED backlight display
Expansion Slot	User accessible MicroSD with 32GB SDHC and up to 512GB SDXC
SIM Slots (X model only)	2 micro SIM
Network Connections	USB 2.0 High Speed OTG (host/client), WLAN, Bluetooth and WWAN
Notification	Audible tone, multi-color LEDs, vibration
Keypad	Numeric (30 key), Function Numeric (42 key), Alpha Numeric (51 key)
Buttons	Buttons: Two programmable side scan keys
Voice	Internal speaker, vibrate alert and Bluetooth wireless headset support; High quality speaker phone;
Audio	Built-in speaker and microphone
Performance Characteristics	
CPU	2.2 GHz Octa-core processor
Operating System	Android 10 with M3 Mobile's StartUp for control over GMS and other services; will support future Android releases.
Memory	4 GB/64 GB Flash
Power	All models ship with rechargeable Li-Ion, 3.6V, 6700mAh battery; full charge under five (5) hours; hot swap support with temporary WWAN/WLAN/Bluetooth session persistence, 2600mAh batteries(optional)
User Environment	
Operating Temp.	-4° F to 140° F/-20° C to 60° C
Storage Temp.	-22°F to 176°F/-30°C to 80°C
Humidity	5% to 95% RH (Non-condensing)
Drop Specifications	Multiple 6 ft./1.8 m drops to concrete across the operating temperature range per MIL-STD-810G
Tumble Specification	3,000 3.3 ft. /1.0 m tumbles; meets and exceeds IEC tumble specification
Sealing	IP65
Vibration	Sine: 4g's peak, 5hz to 2khz, Random: .04g ² /hz, 20hz to 2khz
Thermal Shock	-40° F to 158° F/-40° C to 70° C
Electrostatic Discharge (ESD)	+/- 15kV air, +/-8kV contact discharge +/-8kV indirect contact discharge
Interactive Sensor Technology (IST)	
Light Sensor	Automatically adjusts the brightness of the display
Magnetometer sensor	eCompass automatically detects direction and orientation

Motion Sensors	Gyro Sensor, Accelerometers: for X,Y, and Z movement, and gyroscopes for measuring the extent and rate of rotation in space
Proximity Sensor	Detect the presence of nearby objects without any physical contact, during a telephone call, proximity sensors play a role in detecting accidental touchscreen taps
Data Capture	
Scanning	2D: 0° Scan(Straight Shooter) SE4770 2D: 45° Scan SE4770 LR: 0° Scan(Straight Shooter) SE4850 ERI Optional: SE4750 MR
Rear Camera	16 M pixels auto-focus (AF), PDAF
NFC	ISO 14443 A/B, ISO 15693, Mifare, P2P mode and Card Emulation via Host (HCE) support
Wireless WAN Data AND VOICE COMMUNICATIONS (X model only)	
Radio Frequency Band	LTE FDD: 800/850/900/1800/2100/2600 (1/3/5/7/8/20); LTE TDD: 1600/2300/2500 (38/40/41); UMTS/HSDPA/HSPA+: 850/900/2100(1/5/8); GSM/GPRS/EDGE: 900/1800 (3/8);
GPS	Autonomous, Concurrent GPS; GLONASS; Gallileo; Beidou, and A-GPS
Wireless LAN	
Radio	IEEE 802.11 a/b/g/n/ac/d/e/h/i/k/r/w, IPv4, IPv6, MU-MIMO
Operating Channels (depending on Regulatory)	Channel 1-13 (2412-2472 MHz): 1,2,3,4,5,6,7,8,9,10,11,12,13 Channel 36-165 (5180-5825 MHz): 36,40,44,48,52 56,60,64,100,104,108,112,116,120,124,128,132,136,140,144,149,153,157,161,165 Channel Bandwidth: 20, 40, 80 MHz Actual operating channels/ frequencies and bandwidths depend on regulatory rules and certification agency.
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA3 Personal (SAE); WPA/WPA2 Enterprise (TKIP and AES); WPA3 Enterprise (AES) — EAP-TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC, LEAP and EAP-PWD; WPA3 Enterprise 192-bit Mode (GCMP256) — EAP-TLS; Enhanced Open (OWE)
Fast Roam	PMKID caching; Cisco CCKM; 802.11r; OKC
Wireless PAN	
Bluetooth	Class 2, Bluetooth v4.1 with BR/EDR and Bluetooth Low Energy (BLE) Support
Regulatory	
EMI/EMC	EN 301 489-1; EN 301 489-3; EN 55024; EN 55032 Class A
Electrical Safety	IEC 62368-1, EN 62368-1
RF Exposure	EU: EN 50364, EN 62369-1, EN 50566, EN 62311
Environmental Compliance	
Directive	2011/65/EU, Directive(EU)2015/863
Warranty	
Subject to the terms of M3 Mobile's hardware warranty statement, the US20 series are warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement.	
Recommended Services	

M3 Mobile speed care Essential and Select: Maximize M3 Mobile device availability, device value and operational efficiency with these fully-featured support services that set the industry bar for support.

Footnotes

1. Feature available Q4 2020
 2. Upgrading to new supported version of Android requires the purchase of a M3 SPEED CARE service contract.
-

M3 Speedpack

"M3 Speedpack solutions help you get more value out of our mobile computers by adding functionality as well as simplifying deployment and management of our mobile devices. For more information on these M3 Mobile-only feature."

Application user manual <http://www.m3mobile.net/download/file/743>

Startup PC User Manual <http://www.m3mobile.net/download/file/748>

Startup PC for SOTI <http://www.m3mobile.net/download/file/746>

M3 Speedpack is available on Android only. Features may vary by model and a Support Contract may be required.

Service Center

Chun-ui Techno Park 201-610, 202, Chunui-dong, Wonmi-gu, Bucheon, Gyeonggi-do, 420-857, Korea Tel: +82 32 623 0037 Fax: +82 70 4015 6323

Web site <http://itc.m3mobile.net>

E-mail Information Technology Team: it@m3mobile.co.kr

Customer Service Team: cs@m3mobile.co.kr

Accessories

(Appearance can be changed.)



Head Office

Tel: +82 2 574 0037
Fax: +82 2 558 1253
www.m3mobile.net,
sales@m3mobile.co.kr
sales_kr@m3mobile.co.kr

German Office

Tel +49 61929222148
sales_eu@m3mobile.net

France Office

Mobile +33-(0)686550492
sales_eu@m3mobile.net

UK Office

Tel +49 61929222148
sales_eu@m3mobile.net

Spain Office

Mobile +49 61929222148
sales_eu@m3mobile.net

Turkey Office

Tel +90 070-4801-0358
Mobile +90 533 049 41 30
sales@m3mobile.co.kr

Russia Office

Mobile +7 916 990 90 71
sales@m3mobile.co.kr