TOSHIBA

BV410D BV420D

Desktop printer series

Product brochure

- Toshiba's most advanced desktop print technology is incorporated into the sleekest case design for ultimate user experience.
- Coming with a new powerful and scalable system architecture the BV410D/BV420D future-prooves your investment.
- With a broad set of standard interfaces and optional Wi-Fi or Bluetooth, the BV410D/BV420D easily integrates into even the most complex IT environments.





The ever-changing workplace

Delivering reliability to meet future challenges

Every business is unique. That's why Toshiba offers the most reliable print solutions that meet all your labeling requirements, day after day. Toshiba barcode printers provide connectivity and solutions to adapt to the needs of an ever-changing workplace.

To shiba's barcode printers continue to deliver on our promise of Together Information – our commitment to collaborate with clients to provide tailored, cost-effective solutions that meet your evolving workplace needs.

The strong combination of excellent design & advanced connectivity

Toshiba's most advanced desktop printer consists of five different models, all with a small footprint, intelligent design which brings simplicity and efficiency raising the user experience to the next level. Latest connectivity features enable this printer to be integrated into various networks and, thanks to printer language emulations, into almost every print scenario. The robustness of the printer offers high print quality and performance rivalling the majority of mid-ranged printers.



Smooth design yet outstanding

Designed with the user in mind

Ultimate compactness is core design criteria that led to the creation of the BV410D/BV420D desktop printer range, suitable for versatile applications. With its small footprint and clean case these printers suit retail shops, offices or any workplaces where space is a premium.

Usability clear as day

The sleek design of the BV410D/BV420D eliminates all redundant fussiness and concentrates on delivering clarity of operation to the user. The integrated LCD screen of the BV410D provides clear information and notifications that are emphasised by the colour change of the status LEDs. The user can change main settings directly on the printer whereas the remote operator connections allow the full printer setup from afar.

A model to meet every need

With models available in 203 and 300 dpi versions, also available in black or white cabinets, the BV410D/BV420D suits to fit into almost any operating environment. With the addition of a linerless version enabling the printer to print on adhesive labels with no backing paper reducing waste and keeping the working environment safe and clean.

Future-ready operating system

The redesigned OS platform supports multi printer language emulations, which enables simple integration into complex IT environments. This platform adds not only performance but extends the connectivity and adaptability of the BV410D/BV420D to keep pace with the requirements of an ever-changing workplace.

Speed & efficiency

A series of features makes sure your desktop printer is ready to print labels and receipts quickly and efficiently at the touch of a button. The BV410D/BV420D's productivity is maximised by market leading print speeds of up to 7 inches per second and an advanced CPU which processes your data even quicker. Thanks to the rapid boot-time the printer is ready almost instantly at power-on.

Delivering reliability to meet future challenges

Designed to endure the toughest retail environments the renowned reliability of the BV410D/BV420D printers eliminates almost any downtime – day after day. With built-in AC adapters¹⁾ the Toshiba desktop printers are the perfect fit, ensuring a safe work place.

Key highlights

- Market leading throughput with up to 7 ips
- Compact & sleek design with a small footprint
- Intuitive & clear user experience
- · Vast print languages & emulations
- Huge performance & functionality at a truly low total cost of ownership



Specifications

Models

User Interface

White case BV410D-GS02 BV410D-TS02 203 dpi (8 dots/mm) Resolution 300 dpi (11.8 dots/mm) 2x LED, 3x key, with LCD 2x LED, 3x keys, with LCD User Interface Black case BV420D-GS02 BV420D-TS02 Resolution 203 dpi (8 dots/mm) 300 dpi (11.8 dots/mm)

3x LED, 2x key

Black case linerless cutter BV420D-GL02 Resolution 203 dpi (8 dots/mm) 3x LED, 2x key User Interface Integrated linerless cutter Cutter

General

Print Method Direct thermal Printhead Flat head

Dimensions (W x D x H) BV410D-GS02/TS02 BV420D-GL02

BV420D-GS02/TS02

174 x 288 x 173 mm 174 x 218 x 173 mm

3x LED, 2x key

Weight BV410D-GS02/TS02 BV420D-GL02

BV420D-GS02/TS02

2.0 kg 2.6 kg

128 MB (FROM), 128 MB (SRAM) Memory

Operating Temperature /

Humidity

BV410D-GS02/TS02 BV420D-GL02

BV420D-GS02/TS02

5 - 40°C (41 - 104°F) / 5 - 35°C (41 - 95°F) / 25 - 85% non-condensing 25 - 85% non-condensing relative humidity (RH) relative humidity (RH)

Storage Temperature /

Humidity

-20 - 60°C (-4 - 140°F) / 10 - 90% non-condensing

relative humidity (RH)

Power Supply AC 100 - 240 V, 50/60 Hz

Print

BV410D-GS02/TS02 BV420D-GL02 BV420D-GS02/TS02

Reflective Reflective, transmissive

Max. Print Speed BV410D/420D-GS02 BV410D/420D-TS02

BV420D-GL02

7 ips (177.8 mm/s) 5 ips (127 mm/s)

Max. Print Width BV410D/420D-GS02 BV410D/420D-TS02 BV420D-GL02 108 mm 105.7 mm

Print Length

8 - 997 mm Batch 19.4 - 993 mm¹⁾ Cut Peel-off 23.4 - 150.4 mm¹⁾

Barcodes UPC/EAN/JAN. Code 39. Code 93. Code 128. EAN 128.

NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, POSTNET, RM4SCC, KIX Code, Customer Barcode, GS1

DataBar, USPS Intelligent Mail Barcode

Data Matrix, PDF 417, MaxiCode, QR Code, 2D Codes

Micro PDF 417, Micro QR, GS1 Data Matrix, Aztec Code

Bitmap font, outline font, price font, optional TTF, **Fonts**

writable characters

Media

Alignment Centred

Backing Paper Width BV410D-GS02/TS02 BV420D-GL02

BV420D-GS02/TS02 32 - 102 mm 25.4 - 118 mm

Label Thickness 0.06 - 0.19 mm

Inner Media Core Diameter BV410D-GS02/TS02 BV420D-GL02

BV420D-GS02/TS02

25.4, 38.1, 42, 76.2 mm 38.1 mm

BV420D-GL02

Outer Media Core Diameter BV410D-GS02/TS02

BV420D-GS02/TS02

Standard Max. 127 mm Max. 107 mm Optional

Max. 214 mm

Media Format BV410D-GS02/TS02 BV420D-GL02

BV420D-GS02/TS02

Roll, fanfold Roll

Software & Connectivity

Emulation ZPL II, DPL, SBPL

Printer Driver Windows 10/8.1/8/7 (32/64 bit), Windows Server 2016,

Windows Server 2012 R2/Server 2012/Server 2008 R2, SAP

SDK iOS, Android, Windows, Java

Interface USB 2.0, Ethernet 10/100 Base T (IPv4 & IPv6),

WLAN 802.11a/b/g/n (dual band for 2.4 GHz/5 GHz) $^{1/2}$, Bluetooth V2.1 EDR with MFi certified¹⁾²⁾, Serial port¹⁾

Language Mode TPCL, Basic Command Interpreter (BCI)

Label Software BarTender UltraLite (co-packed)

Options

For BV410D/BV420D Full cutter module³⁾, Partial cutter module³⁾,

Peel-off module³⁾, Serial interface board, Wireless LAN module. Bluetooth module. AC adapter cover, External media stand3)

2) Availability varies from country to country

3) Not available for BV420D-GL02







About Toshiba Tec

Toshiba Tec Corporation is a leading provider of information technology, operating across multiple industries – ranging from retail, education and business services to hospitality and manufacturing. With headquarters in Japan and over 80 subsidiaries worldwide, Toshiba Tec Corporation helps organisations transform the way they create, record, share, manage and display information.

For more information please contact us:

Toshiba Tec Corporation 1-11-1, Osaki, Shinagawa-ku, Tokyo 141-8562, Japan

Website www.toshibatec.com

Γ	٦	Together Information is Toshiba's vision for how people and organisations create, record, share, manage and display ideas and data.
		It is based on our belief that the most successful organisations are those that communicate information in the most efficient way.
		We make that possible through an integrated portfolio of industry-specific solutions, all of which reflect Toshiba's commitment to the future of the planet.
L		